

MS-918-..

Network Type : LV

Low Voltage detector DETEX

Application:

- Check the presence of voltage.
- Checks voltage levels from 12 to 900 V AC, 12 to 1 000 V DC. (According to models)
- Sound and light continuity for a non-live circuit. (threshold of 80 Ohm)
- Search for the polarities of a DC circuit.
- Unipolar phase identification.
- Phase rotation detection check. (two-wire method)
- For indoor / outdoor use.

Features:

- Fitted with IP2X test lead points with retractable trigger tips (MS-918-PG) or retractable sleeves (MS-918 and MS-918-ET). Test lead points Ø 2 mm L: 19 mm (MS-918-L)
- Total safety with hazardous voltage indicator light (> 50 V).
- Protection level: IP65 / IK06.
- Self test button to discern the verification of the good functioning and the continuity function.
- Completely modular and adjustable to eclipse sockets.
- Equipped with a lighting lamp at the measuring point.
- LED display.



Composition:

- MS-918-PG, MS-918-ET: supplied with soft carrying case and belt loop Réf. [M-87285](#)

Optional accessories:

- 2 test plug adapters to be fixed on IP2X test lead points with retractable trigger tips enabling to target test plugs Ø 4 mm. Ref. [DX-04](#).
- Carrying bag with belt loop, Ref. [M-87285](#).
- Holder, Ref. [M-952325](#).

Ref	Weight	Length	Voltages for use		Continuity Test
		Frequency	Operating Voltage AC	Operating Voltage DC	
MS-918	0,21	50 - 400 Hz	12 - 900 V	12 - 1 000 V	80 Ω
MS-918-PG	0,35	50 - 400 Hz	12 - 900 V	12 - 1 000 V	80 Ω
MS-918-ET	0,27	50 - 400 Hz	12 - 900 V	12 - 1 000 V	80 Ω
MS-918-L	0,35	50 - 400 Hz	12 - 900 V	12 - 1 000 V	100 Ω